

IDEAL FOR EXHAUSTS, FUEL LINES AND ELECTRICAL CABLES

Fast, economical and effective installation – slips on like a sock.





Best for tight-fit areas.

The internal fibreglass can withstand constant temperatures up to 530°C

The external silicone layer can withstand;

- A splash of 1650°C molten metal
- Constant temperatures up to 260°C
- Not for putting on turbo applications

PLAIN SILICONE COATED HOSE (ORANGE)

Length Per Metre (minimum 1 metre)

STOCK CODE (ORANGE)	SIZE ID
SHC12	12mm
SHC16	16mm
SHC19	19mm
SHC22	22mm
SHC25	25mm
SHC29	29mm
SHC32	32mm
SHC38	38mm
SHC45	45mm
SHC50	50mm
SHC57	57mm
SHC64	64mm
SHC68	68mm
SHC75	75mm
SHC80	80mm

PLAIN SILICONE COATED HOSE (BLACK)

Length Per Metre (minimum 1 metre)

STOCK CODE (ORANGE)	SIZE ID
SHC12B	12mm
SHC16B	16mm
SHC19B	19mm
SHC22B	22mm
SHC32B	32mm
SHC38B	38mm
SHC57B	57mm
SHC68B	68mm
SHC75B	75mm



